



NHXMH-J/O



Reaction to Fire CPR: Dca-s1,d2,a1

LS0H sheathed single-core cables with improved properties in the event of fire, with solid or stranded conductor for fixed wiring.

Rated voltage

Uo/U 300/500 V

Standards

DIN VDE 0250-214, VDE 0295 cl.1 or cl.2, EN 50267-2-1 (DIN VDE 0482-267-2-1), EN 50267-2-2 (DIN VDE 0482-267-2-2), EN IEC 61034-1 (DIN VDE 0482-1034-1), EN IEC 61034-2 (DIN VDE 0482-1034-2), EN IEC 60332-1-2 (DIN VDE 0482-332-1-2), EN IEC 60332-3-24 (Kat.C), (DIN VDE 0482-332-3-24 (Kat.C)), EN 50575:2014+A1:2016.

Regulation Construction Products

305/2011 EU.

European directives

2014/35/UE (LVD) - 2011/65/CE e 2015/863/EU (RoHS).

Conductor

Annealed plain copper, solid (RE) class 1 or stranded (RM) class 2 EN 60228.

Insulation

Cross-linked Polyethylene type 2X11

Colour of the core: green/yellow (NHXMH-J) or black (NHXMH-O).

Sheath

Thermoplastic halogen-free compound type HM2. Colour: light grey.

Marking

Continuous marking on the sheath: « I.C.E.L. NHXMH-J or NHXMH-O nominal cross section 300/500 V <VDE> production date ». Progressive meter marking.

Guidance for Use

To be installed in buildings or industrial plants where many people and goods are present. As these cables don't develop corrosive and halogen gases in the event of fire, and also the smoke generation is limited and not opaque, the damage caused in case of fire is limited. They can be installed on, in and under the wall-surface, in dry, humid and wet locations, indoors or outdoors but can not be buried directly into the earth.

According to CPR EN 50399



EN 60332-1-2



Minimum installation and handling temp -5 °C



Maximum operating temperature on the conductor

70 °C

Maximum short circuit temperature (max 5 sec)

250 °C

Minimum usage temperature -30 °C



Maximum tensile stress 5 kg/mm²



Minimum internal bending radii 15 times the overall diameter



Low emission of smoke LS0H



Low emission toxic and corrosive gas LS0H



According to RoHS

RoSH free

NHXMH-J/O



Number and nominal cross-sectional area of conductors mm ²	Thickness of insulation specified value mm	Thickness of sheath specified value mm	Mean overall dimensions		Indicative Cable weight g/m	Maximum resistance of conductors at 20 °C ohm/km	Minimum insulation resistance at 70 °C Mohm•km
			MIN mm	MAX mm			
1 x 1,5 RE	0,5	1,4	5,0	8,4	40	12,1	0,008
1 x 2,5 RE	0,5	1,4	5,4	8,8	52	7,41	0,007
1 x 4 RE	0,6	1,4	6,0	9,5	70	4,61	0,006
1 x 6 RE	0,6	1,4	6,4	10,0	93	3,08	0,006
1 x 10 RE	0,7	1,4	7,4	11,3	138	1,83	0,005
1 x 16 RM	0,7	1,4	8,5	12,4	205	1,15	0,004